

## PreCut Soft Top Rubber

By Action Engineering Inc



## Save time and money

- Using PreCut Soft Top Rubber will save you time- Adhesive is already on the rubber.
- No need to go the hardware store to get rollers or chemicals.
- Peel and Stick- then trim excess rubber. It really is that simple.



## Tools needed

- Scotch-Brite™ Pads
- Dawn® Dish Washing Soap
- Hot Water
- Isopropyl Alcohol
- Sharp box knife
- Willing helper
- Roll of pallet paper or rolling pin.
- Mineral spirits
- Paper towels
- Putty knife



## Instructions to replace the Soft Top Rubber with PreCut Soft Top Rubber

- Start by removing the old rubber and clean the remaining adhesive off pallet. Heating up the rubber under the flash will help.
- Then grab a corner of the rubber with Vise Grips or pliers.
- Residue Adhesive can be softened with paper towels and Mineral Spirits.
- Let paper towels soaked with mineral spirits sit on top of the pallets for 20-30 min.
- Scrape off softened adhesive with putty knife. Repeat if necessary.



## Clean Pallet

- After all of the adhesive has been removed, scrub the pallet with the Scotch-Brite™ pad and Dawn® in the hot water.
- Rinse pallet with hot water and dry it off



## Clean Pallet. Ready for new rubber.



### Wipe Pallet with Isopropyl Alcohol

- Please note, this will create a virtually instantaneous bond once the adhesive comes in contact with the pallet. Please be careful.



### Peel Backing off Rubber



### Align with Side Edge of pallet



### Lay Rubber Down

Lay the rubber down as your helper uses a roller to prevent air bubbles.



### Continue to Smooth out with the roller and with your hand.

This helps to make sure that there is 100% contact with the pallet



### Trim excess rubber off.



## Done.

- Let your pallet set up as long as you can, 24-48 hours is recommended.
- You are ready to use your pallets.
- Please try not to burn your pallets. If you do, Action Engineering PreCut rubber will get your pallets back in Action.



See More at

[www.actionengineering.com](http://www.actionengineering.com)

or send email to

[info@actionengineering.com](mailto:info@actionengineering.com)

